




# POWER PACK - AIR COOLED

PREMIUM - 2 PUMP - 3,600 BTUs

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Exterior sight glass to verify glycol bath level.
- Anti-vibration pads reduce motor noise.
- Rugged stainless steel cabinet.



**MMPP4302-PKG**



**L5-30P**



# SPECIFICATIONS

PART NO.	DESCRIPTION	SHIPPING WEIGHT
<b>MMPP4302-PKG</b>	Air cooled power pack, 2 pump and motor	71 kg 157 lbs

## OPERATING PERFORMANCE

<b>COMPRESSOR</b>	1/2 HP	<b>REFRIGERANT</b>	R513a*
<b>BTU PER HOUR</b>	3,600	<b>CHARGE</b>	0.45 kg (16 oz)
<b>PLUG TYPE (NEMA #)</b>	L5-30P	<b>REFRIGERANT RUNNING PRESSURE</b>	18 (low) 140 (high)
<b>CORD LENGTH</b>	8'	<b>BATH CAPACITY</b>	43.5 litre (11.5 gallons)
<b>VOLTAGE</b>	115	<b>PUMP TYPE</b>	Rotary Vane
<b>RUNNING</b>	21A	<b>PUSH IN CONNECTOR</b>	12.7mm (1/2") O.D.

Beginning January 2023: Charged with R513a refrigerant  
 Prior to January 2023: Charged with R134a refrigerant

## DIMENSIONS

