




# POWER PACK - AIR COOLED

PREMIUM - 2 PUMP - 5,100 BTUs

- Engineered by beer-industry experts for performance and value.
- Digital thermostat for accurate glycol bath temperature.
- Expanded urethane foam insulates cabinet to maintain glycol temperature and minimize condensation.
- Exterior sight glass to verify glycol bath level.
- Anti-vibration pads reduce motor noise.
- Rugged stainless steel cabinet.



**MMPP4303-PKG**



**6-20P\***




\*Units manufactured prior to 2/1/2022 were produced with a 6-15P plug.



[www.micromatic.com](http://www.micromatic.com) • 1 (866) 327-4159

**3/4 HP COMPRESSOR**

Job Number: \_\_\_\_\_ Location: \_\_\_\_\_

PART NO.	DESCRIPTION	SHIPPING WEIGHT
	Air cooled power pack, 2 pump and motor	80 kg 175 lbs

**OPERATING PERFORMANCE**

Compressor	3/4 HP
BTU per hour	5,100
Plug Type (NEMA #)	6-20P*
Cord Length	8'
Voltage	208/230
Running	9.5A

Refrigerant	R513a**
Charge	0.79 kg (28 oz)
Refrigerant Running Pressure	18 (low) 140 (high)
Bath Capacity	43.5 litre (11.5 gallons)
Pump Type	Rotary Vane
Push In Connector	12.7mm (1/2") O.D.

\*Units manufactured prior to 2/1/2022 were produced with a 6-15P plug.

\*\*Beginning January 2023: Charged with R513a refrigerant

\*\*Prior to January 2023: Charged with R134a refrigerant

**DIMENSIONS**

